

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
17 January 2002 (17.01.2002)

PCT

(10) International Publication Number  
**WO 02/03933 A2**

- (51) International Patent Classification<sup>7</sup>: **A61K 7/00**
- (21) International Application Number: **PCT/US01/21614**
- (22) International Filing Date: **9 July 2001 (09.07.2001)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
60/217,170 10 July 2000 (10.07.2000) US  
09/850,961 8 May 2001 (08.05.2001) US
- (71) Applicant: **THE PROCTER & GAMBLE COMPANY**  
[US/US]; One Procter & Gamble Plaza, Cincinnati, OH  
45202 (US).
- (72) Inventors: **VATTER, Michael, Lee**; 4159 California  
Road, Okeana, OH 45053 (US). **SUNKEL, Jorge, Max**;  
460 Fairview Place, Cincinnati, OH 45219 (US). **MOT-  
LEY, Curtis, Bobby**; 8032 St. Matthew Drive, West  
Chester, OH 45069 (US).
- (74) Agents: **REED, T., David et al.**; The Procter & Gam-  
ble Company, 5299 Spring Grove Avenue, Cincinnati, OH  
45217-1087 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AT  
(utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA,  
CH, CN, CO, CR, CU, CZ, CZ (utility model), DE, DE  
(utility model), DK, DK (utility model), DM, DZ, EC, EE,  
EE (utility model), ES, FI, FI (utility model), GB, GD, GE,  
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ,  
LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,  
MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI,  
SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG,  
UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,  
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,  
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**  
— *without international search report and to be republished  
upon receipt of that report*
- For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.*



**WO 02/03933 A2**

(54) Title: **ANHYDROUS COSMETIC COMPOSITIONS**

(57) Abstract: An anhydrous skin treatment composition is provided which includes a crosslinked emulsifying siloxane elastomer, at least 20 % humectant and a volatile siloxane. Inclusion of the elastomer provides a non-traditional smooth/silky feel to the skin upon application with a non-draggy rub in.

ANHYDROUS COSMETIC COMPOSITIONS  
CROSS REFERENCE TO RELATED APPLICATION

This application claims the benefit of U.S. Provisional Application No. 60/217,170, filed July 10, 2000.

FIELD OF THE INVENTION

The invention relates to anhydrous cosmetic compositions comprising emulsifying elastomeric silicones of specific particle size and viscosity.

BACKGROUND OF THE INVENTION

Emollients including organic esters and hydrocarbons, especially petrolatum, have long been used medicinally as skin conditioning agents. These substances are second only to water as moisturizing ingredients of choice. They function primarily as an occlusive barrier. The water content of the outer layers of human skin stratum corneum is a controlling factor in the appearance of dry skin symptoms. When the stratum corneum contains an adequate amount of water within the range of ten to twenty percent, the skin remains flexible. However, when the water content falls below ten percent the stratum corneum often becomes brittle and rough and can exhibit scaling and cracking.

The stratum corneum receives its water from the deep layers of the epidermis by diffusion or when it is brought into direct contact with water. The diffusion process is controlled by the water content of the skin as well as the concentration gradient. In a very dry environment, the water loss from the external skin layers can be significant and often exceeds the rate of replacement by diffusion. An occlusive or semi-occlusive barrier substance placed on the surface of the skin acts to retard water loss to the environment. It also allows the skin surface to rehydrate via a diffusion mechanism.

While there are many effective and economical skin-conditioning agents, they nevertheless suffer from certain disadvantages.

Often the emollient types are delivered as water-in-oil emulsions. It is difficult to attain the critical formula balance between oil and water phases to an extent sufficient to ensure long-term storage stability. One part of this critical balance is the internal phase volume. A critical volume must be obtained to maximize the chemical and physical interactions that produce and stabilize the system. If this critical volume is not balanced properly the product may suffer from viscosity change and eventual phase separation. Usually the optimum volume is quite large which limits the external phase volume size, and gives the system a draggy unfavorable slow

break attribute. This critical internal phase volume restriction can reduce functionality and add unfavorable feel characteristics.

Anhydrous systems avoid emulsion stability problems. Unfortunately other aesthetic issues arise with anhydrous systems. Not all oily phase materials are compatible at high concentration. Moreover, occlusive agents such as petrolatum are relatively greasy. They suffer the disadvantage of transfer onto clothing and are not easily removed from the skin by washing with soap. Neither do they allow for adequate penetration into the epidermis.

New systems are needed which avoid such problems as greasy feel and which address the "transfer" typically associated with anhydrous products.

Accordingly, one aspect of the present invention is to provide cosmetic compositions that are anhydrous yet provides improved skin-feel properties.

Another aspect of the present invention is to provide a skin treatment composition that has stability against phase separation even under freeze/thaw cycling.

Still another aspect of the present invention is to provide a skin treatment composition which achieves a smooth non-draggy rub-in upon initial application to the skin and which is not easily removed from the skin with water.

These and other aspects of the present invention will become more readily apparent from consideration of the following summary and detailed description.

#### SUMMARY OF THE INVENTION

The present invention relates to a non-solid, anhydrous cosmetic compositions comprising:

- (i) from about 0.1 to about 30% of emulsifying crosslinked siloxane elastomer, preferably having a particle size of from above 10 to about 200 microns;
  - (ii) from about 10 to about 80% of a solvent for the crosslinked siloxane elastomer, preferably wherein the solvent forms a gel having a viscosity greater than 100,000 cps, more preferably at least 200,000 cps, most preferably at least 500,000 cps, and, optimally, at least 700,000 cps at 25°C as measured by a Brookfield LV Viscometer (size 4 bar, 60 rpm, 0.3 sec.); and
  - (iii) at least about 20% of a humectant
- wherein the compositions contain less than about 1% water, preferably 0% water, and, preferably, wherein the compositions have a yield point of from about 50, preferably from about 100, more preferably from about 200 to about 5,000, preferably to about 4000, more preferably to about 2000 Pa.

Also claimed herein are non-solid, anhydrous cosmetic compositions comprising:

- (i) from about 0.1 to about 30% of emulsifying crosslinked siloxane elastomer, preferably having a viscosity of from above 20,000 to about 6,000,000 cps;
  - (ii) from about 10 to about 80% of a solvent for the crosslinked siloxane elastomer, preferably wherein the solvent forms a gel having a viscosity greater than 100,000 cps, more preferably at least 200,000 cps, most preferably at least 500,000 cps, and, optimally, at least 700,000 cps at 25°C as measured by a Brookfield LV Viscometer (size 4 bar, 60 rpm, 0.3 sec.); and
  - (iii) at least (or greater than) about 20% of a humectant
- wherein the compositions contain less than 1% water, preferably 0% water, and, preferably, wherein the compositions have a yield point of from about 50, preferably from about 100, more preferably from about 200 to about 5,000, preferably to about 4000, more preferably to about 2000 Pa.

#### DETAILED DESCRIPTION OF THE INVENTION

As used herein, the term "cosmetics" includes make-up, foundation, and skin care products. The term "make-up" refers to products that leave color on the face, including foundation, blacks and browns, i.e., mascara, concealers, eye liners, brow colors, eye shadows, blushers, lip colors, powders, solid emulsion compact, and so forth. "Skin care products" are those used to treat or care for, or somehow moisturize, improve, or clean the skin. Products contemplated by the phrase "skin care products" include, but are not limited to, adhesives, bandages, toothpaste, anhydrous occlusive moisturizers, antiperspirants, deodorants, personal cleansing products, powder laundry detergent, fabric softener towels, occlusive drug delivery patches, nail polish, powders, tissues, wipes, hair conditioners-anhydrous, shaving creams and the like. The term "foundation" refers to liquid, creme, mousse, pancake, compact, concealer or like product created or reintroduced by cosmetic companies to even out the overall coloring of the skin. Foundation is manufactured to work better over moisturized and/or oiled skin. As used herein, "excess moisture" means an undesirable and/ or unhealthy level of bodily fluids deposited on human skin. The compositions of the present invention also provide good make-up removal. The compositions of the present invention are especially useful in removal make-up compositions such as that disclosed in US Patent 6,019,962 to Rabe et al., which patent is herein incorporated by reference in its entirety.

The term "ambient conditions" as used herein refers to surrounding conditions under about one atmosphere of pressure, at about 50% relative humidity, and at about 25°C, unless otherwise specified.

The term "yield point," as used herein is non-directional and refers to initial resistance to flow under applied stress; and is measured using Haake Controlled Stress Rheometer RS150 with a 35mm/4 deg. cone and plate.

As used herein, the term "comprising" means that the composition can contain other ingredients which are compatible with the composition and which preferably do not substantially disrupt the compositions of the present invention. The term encompasses the terms "consisting of" and "consisting essentially of".

As used herein, the term "non-solid" refers to compositions having or maintaining the qualities or properties of a liquid such as gels, semi-solids and liquids.

Unless otherwise indicated, all percentages and ratios used herein are by weight of the total composition. All weight percentages, unless otherwise indicated, are on an active weight basis. All measurements made are at 25°C, unless otherwise designated.


#### Crosslinked Siloxane Elastomer

An essential component of the present invention is the cross-linked organopolysiloxane elastomer. The crosslinked organopolysiloxane elastomers can be either partially or completely cross-linked. They are generally emulsifiers. They can notably be chosen from the crosslinked polymers described in US Patents 5,412,004 (issued 5/2/95); 5,837,793 (issued 11/17/98); and 5,811,487 (issued 9/22/98), all of which are herein incorporated by reference in their entirety. These organopolysiloxanes are obtained by the addition polymerization of the following compounds (I) and (II):

(I) an organohydrogen polysiloxane having formula (I):



in which  $\text{R}^1$  represents a substituted or unsubstituted alkyl, aryl or aralkyl group, comprising 1-18 carbon atoms, or a halogenated hydrocarbon group;  $\text{R}^2$  represents a group:



in which  $\text{R}^1$  is a hydrogen atom, a saturated aliphatic hydrocarbon group having 1-10 carbon atoms or a  $-(\text{CO})-\text{R}^5$  group where  $\text{R}^5$  is a saturated aliphatic hydrocarbon group having 1-5 carbon atoms; d is a whole number from 2 to 200, and e is a whole number from 0 to 200, provided that d + e is a number in the range of 3 to 200, and n is a number in the range of 2 to 6, a is a value

satisfying the inequality:  $1.0 \leq a \leq 2.5$ ,  $b$  is a value satisfying the inequality:  $0.001 \leq b \leq 1.0$  and  $c$  is a value satisfying the inequality:  $0.001 \leq c \leq 1.0$ ;

or an organohydrogen polysiloxane represented by the following formula (2):



- 5 in which  $h$  is a whole number in the range of 2 to 200,  $i$  is a whole number in the range of 0 to 200, provided that  $h + i$  is a number in the range of 3 to 200, and  $m$  is a number in the range of 2 to 6,

or an organopolysiloxane represented by the following formula (B):



- 10 in which  $\text{R}^1$  has the same meaning as in formula (1),  $\text{R}^4$  is a monovalent hydrocarbon group having an unsaturated aliphatic bond at the end and containing 2-10 carbon atoms,  $j$  is a value satisfying the inequality:  $1.0 \leq j \leq 3.0$  and  $k$  is a value satisfying the inequality  $0.001 \leq k \leq 1.5$ , or a mixture of the polyoxyalkylene having formula (A) or of the organopolysiloxane having formula (B), where at least one organohydrogen polysiloxane having formula (1) or at least one  
15 polyoxyalkylene having formula (A) is contained as an essential element of the addition polymerization.

It is preferred for the organopolysiloxane to be in a mixture with a silicone oil and/or polyol, and to be prepared directly in such a mixture. The silicone oil preferably has a viscosity equal to or less than 500 cSt at 25°C. According to an embodiment of the invention, the  
20 organopolysiloxane elastomer is prepared from 100 parts by weight of the constituents defined above and 3-200 parts by weight of a silicone oil having a viscosity equal to or less than 100 cSt at 25°C, and/or a polyol. The silicone oil can be a volatile or nonvolatile silicone oil or a mixture of a volatile silicone oil and a nonvolatile silicone oil.

The organopolysiloxanes of the invention are obtained, in particular, according to the  
25 protocol of Examples 3, 4 and 8 of the document EP-A-545002 (or US-5,412,004) and from the examples of the document US-A-5,81,487.

The organopolysiloxanes of the composition of the invention contain one or more oxyalkylenated group(s) and in particular oxyethylenated (OE) group(s), for example, 1-40 oxyalkylenated units and, more advantageously, 1-20 oxyalkylenated units, that can form  
30 polyoxyalkylene, notably polyoxyethylene chains. These groups can be branches, at the end of the chain, or intended to link two parts of the silicone structure. The silicon atoms bearing these groups are approximately 1-10 in number.

Although the invention concerns more particularly organopolysiloxanes with oxyethylenated group(s), it can also concern the organopolysiloxanes with oxypropylenated group(s). The organopolysiloxanes can comprise simultaneously one or more oxyethylenated group(s), 1-20 (OE), for example, and one or more oxypropylenated group(s) (OP), 0-20, for example; these organopolysiloxanes are also called organopolysiloxanes with alkylethoxy-propylenated group(s). It is preferred for the number of oxyethylenated groups to be larger than the number of oxypropylenated groups.

As the partially or completely crosslinked organopolysiloxane comprising a polyoxyethylenated and/or polyoxypropylenated chain one can mention, for example, the product marketed by Shin-Etsu under the name KSG21, KSG31, KSG31x and KSG32 or by Dow Corning under the name DC 9011. One can also mention the product of Example 3 of US Patent No. US-5,412,004, containing approximately 33 wt% of organopolysiloxane and approximately 67 wt% of silicone oil having a viscosity of 6 cSt.

Also useful herein are polyoxyalkylene modified elastomers formed from divinyl compounds, particularly siloxane polymers with at least two free vinyl groups, reacting with Si-H linkages on a polysiloxane backbone. Preferably, the elastomers are dimethyl polysiloxanes crosslinked by Si-H sites on a molecularly spherical MQ resin.

Amounts of the elastomer may range from about 0.1 to about 30%, optimally from about 1 to about 15%, most preferably from about 3 to about 10% by weight.

#### Solvent for the Emulsifying Crosslinked Siloxane Elastomer

The compositions of the present invention comprise a solvent for the emulsifying crosslinked organopolysiloxane elastomer described hereinbefore. The solvent, when combined with the cross-linked organopolysiloxane elastomer particles, serves to suspend and swell the elastomer particles to provide an elastic, gel-like network or matrix. The solvent for the emulsifying cross-linked siloxane elastomer is liquid under ambient conditions, and preferably has a low viscosity to provide for improved spreading on the skin. The viscosity of the elastomer gel is preferably greater than 100,000 cps, more preferably at least about 250,000 cps, optimally from about 300,000 to about 6,000,000 cps at 25°C as measured by a Brookfield LV Viscometer (size 4 bar, 60 rpm, 0.3 sec.).

Concentrations of the solvent in the cosmetic compositions of the present invention will vary primarily with the type and amount of solvent and the emulsifying cross-linked siloxane elastomer employed. Preferred concentrations of the solvent are from about 10% to about 90%,

preferably from about 20% to about 80%, more preferably from about 30% to about 70%, by weight of the composition.

The solvent for the emulsifying cross-linked siloxane elastomer comprises one or more liquid carriers suitable for topical application to human skin. These liquid carriers may be organic, silicone-containing or fluorine-containing, volatile or non-volatile, polar or non-polar, provided that the liquid carrier forms a solution or other homogenous liquid or liquid dispersion with the selected emulsifying cross-linked siloxane elastomer at the selected siloxane elastomer concentration at a temperature of from about 28°C to about 250°C, preferably from about 28°C to about 100°C, preferably from about 28°C to about 78°C. The solvent for the emulsifying cross-linked siloxane elastomer preferably has a solubility parameter of from about 3 to about 13  $(\text{cal}/\text{cm}^3)^{0.5}$ , more preferably from about 5 to about 11  $(\text{cal}/\text{cm}^3)^{0.5}$ , most preferably from about 5 to about 9  $(\text{cal}/\text{cm}^3)^{0.5}$ . Solubility parameters for the liquid carriers or other materials, and means for determining such parameters, are well known in the chemical arts. A description of solubility parameters and means for determining them are described by C. D. Vaughan, "Solubility Effects in Product, Package, Penetration and Preservation" 103 Cosmetics and Toiletries 47-69, October 1988; and C. D. Vaughan, "Using Solubility Parameters in Cosmetics Formulation", 36 J. Soc. Cosmetic Chemists 319-333, September/October, 1988, which articles are incorporated herein by reference.


The solvent preferably includes volatile, non-polar oils; non-volatile, relatively polar oils; non-volatile, non-polar oils; and non-volatile paraffinic hydrocarbon oils; each discussed more fully hereinafter. The term "non-volatile" as used herein refers to materials which exhibit a vapor pressure of no more than about 0.2 mm Hg at 25°C. at one atmosphere and/or to materials which have a boiling point at one atmosphere of at least about 300°C. The term "volatile" as used herein refers to all materials that are not "non-volatile" as previously defined herein. The phrase "relatively polar" as used herein means more polar than another material in terms of solubility parameter; i.e., the higher the solubility parameter the more polar the liquid. The term "non-polar" typically means that the material has a solubility parameter below about  $6.5 (\text{cal}/\text{cm}^3)^{0.5}$ .

#### 1. Non-polar, Volatile Oils

The non-polar, volatile oil tends to impart highly desirable aesthetic properties to the compositions of the present invention. Consequently, the non-polar, volatile oils are preferably utilized at a fairly high level. Non-polar, volatile oils particularly useful in the present invention are selected from the group consisting of silicone oils; hydrocarbons; and mixtures thereof.



Such non-polar, volatile oils are disclosed, for example, in *Cosmetics, Science, and Technology*, Vol. 1, 27-104 edited by Balsam and Sagarin, 1972. The non-polar, volatile oils useful in the present invention may be either saturated or unsaturated, have an aliphatic character and be straight or branched chained or contain alicyclic or aromatic rings. Examples of preferred non-polar, volatile hydrocarbons include polydecenes such as isododecane and isodecane (e.g., Permethyl-99A which is available from Presperse Inc.) and the C7 -C8 through C12 -C15 isoparaffins (such as the Isopar Series available from Exxon Chemicals). Non-polar, volatile liquid silicone oils are disclosed in U.S. Patent 4,781,917 issued to Luebke et al. on Nov. 1, 1988, herein incorporated by reference in its entirety. Additionally, a description of various volatile silicones materials is found in Todd et al., "Volatile Silicone Fluids for Cosmetics", *Cosmetics and Toiletries*, 91:27-32 (1976), herein incorporated by reference in its entirety. Particularly preferred volatile silicone oils are selected from the group consisting of cyclic volatile silicones corresponding to the formula:



wherein n is from about 3 to about 7; and linear volatile silicones corresponding to the formula:



wherein m is from about 1 to about 7. Linear volatile silicones generally have a viscosity of less than about 5 centistokes at 25°C., whereas the cyclic silicones have viscosities of less than about 10 centistokes at 25°C. Highly preferred examples of volatile silicone oils include cyclomethicones of varying viscosities, e.g., Dow Corning 200, Dow Corning 244, Dow Corning 245, Dow Corning 344, and Dow Corning 345, (commercially available from Dow Corning Corp.); SF-1204 and SF-1202 Silicone Fluids (commercially available from G.E. Silicones), GE 7207 and 7158 (commercially available from General Electric Co.); and SWS-03314 (commercially available from SWS Silicones Corp.).

## 2. Relatively Polar, Non-volatile oils

The non-volatile oil is "relatively polar" as compared to the non-polar, volatile oil discussed above. Therefore, the non-volatile co-solvent is more polar (i.e., has a higher solubility parameter) than at least one of the non-polar, volatile oils. Relatively polar, non-volatile oils potentially useful in the present invention are disclosed, for example, in *Cosmetics, Science, and Technology*, Vol. 1, 27-104 edited by Balsam and Sagarin, 1972; U.S. Patents 4,202,879 issued to

Shelton on May 13, 1980; and 4,816,261 issued to Luebbe et al. on Mar. 28, 1989, all of which are herein incorporated by reference in their entirety. Relatively polar, non-volatile oils useful in the present invention are preferably selected from the group consisting of silicone oils; hydrocarbon oils; fatty alcohols; fatty acids; esters of mono and dibasic carboxylic acids with  
5 mono and polyhydric alcohols; polyoxyethylenes; polyoxypropylenes; mixtures of polyoxyethylene and polyoxypropylene ethers of fatty alcohols; and mixtures thereof. The relatively polar, non-volatile co-solvents useful in the present invention may be either saturated or unsaturated, have an aliphatic character and be straight or branched chained or contain alicyclic or aromatic rings. More preferably, the relatively polar, non-volatile liquid co-solvent are  
10 selected from the group consisting of fatty alcohols having from about 12-26 carbon atoms; fatty acids having from about 12-26 carbon atoms; esters of monobasic carboxylic acids and alcohols having from about 14-30 carbon atoms; esters of dibasic carboxylic acids and alcohols having from about 10-30 carbon atoms; esters of polyhydric alcohols and carboxylic acids having from about 5-26 carbon atoms; ethoxylated, propoxylated, and mixtures of ethoxylated and  
15 propoxylated ethers of fatty alcohols with from about 12-26 carbon atoms and a degree of ethoxylation and propoxylation of below about 50; and mixtures thereof. More preferred are propoxylated ethers of C14 -C18 fatty alcohols having a degree of propoxylation below about 50, esters of C2 -C8 alcohols and C12-C26 carboxylic acids (e.g. ethyl myristate, isopropyl palmitate), esters of C12-C26 alcohols and benzoic acid (e.g. Finsolv TN supplied by Finetex),  
20 diesters of C2-C8 alcohols and adipic, sebacic, and phthalic acids (e.g., diisopropyl sebacate, diisopropyl adipate, di-n-butyl phthalate), polyhydric alcohol esters of C6 -C26 carboxylic acids (e.g., propylene glycol dicaprate/dicaprylate, propylene glycol isostearate); and mixtures thereof. Even more preferred are branched-chain aliphatic fatty alcohols having from about 12-26 carbon atoms. Even more preferred are isocetyl alcohol, octyldecanol, octyldodecanol and  
25 undecylpentadecanol; and most preferred is octyldodecanol. Such preferred aliphatic fatty alcohols are particularly useful in combination with the volatile liquid silicone oils discussed herein to adjust the average solubility of the solvent.

### 3. Non-polar, Non-volatile oils

In addition to the liquids discussed above, the solvent for the emulsifying cross-linked  
30 siloxane elastomer may optionally include non-volatile, non-polar oils. Typical non-volatile, non-polar emollients are disclosed, for example, in *Cosmetics, Science, and Technology*, Vol. 1, 27-104 edited by Balsam and Sagarin, 1972; U.S. Patents 4,202,879 issued to Shelton on May 13, 1980; and 4,816,261 issued to Luebbe et al. on Mar. 28, 1989, both of which are herein

incorporated by reference. The non-volatile oils useful in the present invention are essentially non-volatile polysiloxanes, paraffinic hydrocarbon oils, and mixtures thereof. The polysiloxanes useful in the present invention selected from the group consisting of polyalkylsiloxanes, polyarylsiloxanes, polyalkylarylsiloxanes, poly-ethersiloxane copolymers, and mixtures thereof.

5 Examples of these include polydimethyl siloxanes having viscosities of from about 1 to about 100,000 centistokes at 25°C. Among the preferred non-volatile silicone emollients useful in the present compositions are the polydimethyl siloxanes having viscosities from about 2 to about 400 centistokes at 25°C. Such polyalkylsiloxanes include the Viscasil series (sold by General Electric Company) and the Dow Corning 200 series (sold by Dow Corning Corp.). Polyalkylarylsiloxanes

10 include polymethylphenyl siloxanes having viscosities of from about 15 to about 65 centistokes at 25°C. These are available, for example, as SF 1075 methyl-phenyl fluid (sold by General Electric Company) and 556 Cosmetic Grade Fluid (sold by Dow Corning Corp.). Useful polyethersiloxane copolymers include, for example, a polyoxyalkylene ether copolymer having a viscosity of about 1200 to 1500 centistokes at 25°C. Such a fluid is available as SF1066 organosilicone surfactant

15 (sold by General Electric Company). Polysiloxane ethylene glycol ether copolymers are preferred copolymers for use in the present compositions.

Non-volatile paraffinic hydrocarbon oils useful in the present invention include mineral oils and certain branched-chain hydrocarbons. Examples of these fluids are disclosed in U.S. Patent 5,019,375 issued to Tanner et al. on May 28, 1991, herein incorporated by reference in its

20 entirety. Preferred mineral oils have the following properties:

- (1) viscosity from about 5 centistokes to about 70 centistokes at 40°C.;
- (2) density between about 0.82 and 0.89 g/cm<sup>3</sup> at 25°C;
- (3) flash point between about 138°C and about 216°C; and
- (4) carbon chain length between about 14 and about 40 carbon atoms.

25 Preferred branched chain hydrocarbon oils have the following properties:

- (1) density between about 0.79 and about 0.89 g/cm<sup>3</sup> at 20°C
- (2) boiling point greater than about 250°C; and
- (3) flash point between about 110°C and about 200°C.

Particularly preferred branched-chain hydrocarbons include Permethyl 103 A, which contains an

30 average of about 24 carbon atoms; Permethyl 104A, which contains an average of about 68 carbon atoms; Permethyl 102A, which contains an average of about 20 carbon atoms; all of which may be purchased from Permethyl Corporation; and Ethylflo 364 which contains a mixture of 30 carbon atoms and 40 carbon atoms and may be purchased from Ethyl Corp.

When used herein, volatile or non-volatile hydrocarbon oils are preferably present at concentrations less than 30%, more preferably, from about 1% to about 25%, most preferably from about 1% to about 15%.

Additional solvents useful herein are described in US Patent 5,750,096 to Gerald J. Guskey et al., issued May 12, 1998, herein incorporated by reference in its entirety.

#### Humectant

The compositions of the present invention additionally comprise a humectant. Humectants are polyhydric alcohols intended for moisturizing, reducing scaling and stimulating removal of built-up scale from the skin. Typical polyhydric alcohols include polyalkylene glycols and more preferably alkylene polyols and their derivatives. Illustrative are propylene glycol, dipropylene glycol, polypropylene glycol, polyethylene glycol, sorbitol, hydroxypropyl sorbitol, hexylene glycol, 1,3-butylene glycol, 1,2,6-hexanetriol, ethoxylated glycerin, propoxylated glycerin and mixtures thereof. Most preferably the humectant is glycerin. Amounts of humectant may range anywhere from at least 20% humectant to, optimally, between 25% to 50% by weight humectant.

### OPTIONAL INGREDIENTS

#### Shine Control Agents

Cosmetic products that improve and/or regulate the condition of the shiny appearance of skin are increasingly popular with consumers and are referred to herein as "shine control agents". Shine control agents may be included in the compositions of the present invention.

A frequent, undesirable condition is "oily skin", which results from the excessive amount of sebum and sweat that is excreted onto the skin. Sebum is an oily mixture, composed principally of squalene, triglycerides, fatty acids and wax esters. Sebum is produced in the sebaceous glands of the skin. Oily skin is associated with a shiny, undesirable appearance and disagreeable tactile sensation. Sweat is predominantly water with trace quantities of dissolved inorganic salts such as sodium chloride and potassium chloride.

Typically, shine control agents are porous in nature. These agents, when applied to the skin provide a reservoir to absorb excess moisture into the pores, hence reducing the visible quantity of moisture on the skin.

Without being limited by theory, it is believed that it is preferable to combine the use of effective porous, absorbent materials with non-absorbing spherical materials. The latter emphasizes the effect of diffuse reflection over problematic specular reflection, causing an

optical modification to the skin and hence a reduction in the shiny appearance of the skin. The combination of shine control agents and non-absorbing spherical particles is preferable because it allows development of a product with optimum shine control as well as providing a product with the best tactile sensory performance.

5           Suitable shine control agents include, but are not limited to, silicas, magnesium aluminum silicates, talc, sericite and various organic copolymers. Particularly effective shine control agents include silicates or carbonates that are formed by reaction of a carbonate or silicate with the alkali (IA) metals, alkaline earth (IIA) metals, or transition metals, and silicas (silicon dioxide). Preferred shine control agents are selected from the group consisting of calcium  
10   silicates, amorphous silicas, calcium carbonates, magnesium carbonates, zinc carbonates, and combinations thereof. Some specific examples of the silicates and carbonates useful in this present invention are more fully explained in Van Nostrand Reinhold's Encyclopedia of Chemistry, 4<sup>th</sup> Ed. pp155, 169, 556, and 849 (1984).

          Synthetic versions of the shine control agents, particularly silicates, are preferred. .  
15   Examples of synthetic silicates useful in the present invention are Hubersorb 250@ or Hubersorb 600@, available from JM Huber.

          Shine control agents that primarily comprise silicas are preferred over those materials comprising mainly silicates and/ or carbonates when used for moisture and shine control. Most preferred silicas are in the form of microspheres and/ or ellipsoids, as they have been found to  
20   contribute good skin feel characteristics in addition to efficient moisture absorption. Silica ellipsoids useful in the present invention are available from DuPont as ZELEC Sil and Kobo as Silica Shells. Silica microspheres are available from Kobo as MSS-500, MSS500/3, MSS-500H, MSS500/3N, MSS-500N and MSS 500/ 3N; Presperse as Spheron L1500, Spheron P1500. Fumed versions of silica can also be used with Aerosil from Degussa and Cab-O-Sil from Cabot  
25   both being particularly useful.

          Amongst the silicate series, magnesium aluminum silicates are useful, in particular Sebumase, available from Miyoshi Kasei.

          When silicas, particularly silica ellipsoids and silica microspheres are intended to be the main means for moisture absorption, it is preferred that the absorbent powder comprise from  
30   about 1% to about 40%; more preferably from about 1% to about 25%, and most preferably from about 2% to about 10%, by weight of the composition, of silicas.

Starch-based materials may also be used as shine control agents. Useful examples are Natrosorb W and Natrosorb HFW, DryFlo plus and DryFlo AF pure from National Starch and Chemical Company.

Also found to be useful are methacrylate-based polymeric materials. They can be used  
5 either in conjunction with a dimethicone copolymer or as methacrylate-based copolymers. Specifically, useful examples are: Microsponge 5640 w. Glycerin, Polytrap 6603 available from Enhanced Derm technologies; DSPCS-I2 series and SPCAT-I2 from Kobo; Poly-Pore 200 series from Amcol.

Optionally, yet preferably, the compositions of the present invention contain spherical  
10 particles having an average particle size diameter of 10 or greater, preferably greater than 15, more preferably greater than 20 microns. The particle diameter is understood to be that of elementary or primary particles.

Preferred spherical particles include, but are not limited, to polymeric particles chosen from the methylsilsesquioxane resin microspheres such as for example those sold by Toshiba  
15 silicone under the name Tospearl 145A; microspheres of polymethylmethacrylates such as those sold by Seppic under the name Micropearl M 100; the spherical particles of crosslinked polydimethylsiloxanes, especially such as those sold by Dow Corning Toray Silicone under the name Trefil E 506C or Trefil E 505C, sphericle particles of polyamide and more specifically Nylon 12, especially such as those sold by Atochem under the name Orgasol 2002D Nat C05,  
20 polystyrene microspheres such as for example those sold by Dyno Particles under the name Dynospheres, ethylene acrylate copolymer sold by Kobo under the name FloBead EA209 and mixtures thereof. Also found to be useful is Ronasphere LDP from Kobo Inc

Preferably the spherical particles are present at a concentration of from about 0% to about 40%, more preferably from about 5% to about 35%, most preferably from about 8% to  
25 about 30%.

#### Film Forming Agents

Film forming agents may be optionally included in the compositions of the present invention to aid film substantivity and adhesion to the skin. Improving the long wear and non-  
30 transfer performance of the present compositions is quite desirable. Water-soluble, water insoluble, and water dispersible film forming agents can be used in the internal and external phases of the present compositions to give the desired end benefit.

Preferably, the compositions comprise from about 0% to about 20%, more preferably,

from about 0.1% to about 10%, and most preferably, from about 0.1% to about 5%, by weight of the composition, of the film-forming agent.

Suitable film forming agents include:

- 5 1) organic silicone resins, fluorinated silicone resins, copolymers of organic silicone resins, e.g., trimethylsiloxysilicate from GE (SR1000), GE's copolymers of silicone resins, e.g., SF1318 (silicone resin and an organic ester of isostearic acid copolymer) and CF1301 (silicone resin and alpha methyl styrene copolymer), Dow Corning's pressure sensitive adhesives - copolymers of silicone resins and various PDMS's (BIO-PSA series); and
- 10 2) acrylic and methacrylic polymers and resins, silicone-acrylate type copolymers and fluorinated versions of, including - silicones plus polymer SA70 from 3M, KP545 from Shin-Etsu, alkyl-acrylate copolymers, e.g., KP 561 and 562 from Shin-Etsu;
- 3) decene/butene copolymer from Collaborative Labs;
- 15 4) polyvinyl based materials, e.g., PVP, PVP/VA, including Antaron/Ganex from ISP (PVP/Triacontene copolymer), Luviskol materials from BASF;
- 5) polyurethanes, e.g., the Polyderm series from Alzo including but not limited to Polyderm PE/PA, Polyderm PPI-SI-WS, Polyderm PPI-GH, Luviset P.U.R. from BASF;
- 20 6) polyquaternium materials, e.g., Luviquat series from BASF
- 7) acrylates copolymers and acrylates/acrylamide copolymers, e.g., Luvimer and Ultrahold series, both available from BASF;
- 8) styrene based materials; and
- 9) chitosan and chitosan based materials including cellulose and cellulose-based materials.
- 25

Such film formers are disclosed for example in the International Cosmetic Ingredient Dictionary and Handbook, Seventh Edition, Vol 2, 1636-1638.

#### Skin Conditioning Agent

- 30 Optionally, the compositions of the present invention can further comprise an additional skin-conditioning agent. These agents may be selected from exfoliants, emollients and mixtures thereof.

Exfoliants according to the present invention may be selected from C2-C30 alpha-hydroxycarboxylic acids, beta-hydroxycarboxylic acids and salts of these acids. Most preferred are glycolic, lactic and salicylic acids and their ammonium salts. Amounts of the exfoliants may range from 1 to 15%, preferably from 2 to 10% by weight.

5 A wide variety of C2-C30 alpha-hydroxycarboxylic acids may be employed. Suitable examples of which include:

alpha -hydroxyethanoic acid  
alpha -hydroxypropanoic acid  
alpha -hydroxyhexanoic acid  
10 alpha -hydroxyoctanoic acid  
alpha -hydroxydecanoic acid  
alpha -hydroxydodecanoic acid  
alpha -hydroxytetradecanoic acid  
alpha -hydroxyhexadecanoic acid  
15 alpha -hydroxyoctadecanoic acid  
alpha -hydroxyeicosanoic acid  
alpha -hydroxydocosanoic acid  
alpha -hydroxyhexacosanoic acid, and  
alpha -hydroxyoctacosanoic acid

20 When the conditioning agent is an emollient it may be selected from hydrocarbons, fatty acids, fatty alcohols and esters. Isononyl isononanoate is the most preferred hydrocarbon type of emollient conditioning agent. Other hydrocarbons that may be employed include mineral oil, polyolefins such as polydecene, and paraffins such as isohexadecane (e.g. Permethyl 99 Registered TM and Permethyl 101 Registered TM). Preferably, the compositions of the present  
25 invention are substantially free of semi-solid hydrocarbons such as petrolatum, lanolin and lanolin derivatives, sterols (e.g., ethoxylated soya sterols), high molecular weight polybutenes and cocoa butter. By "substantially free," as used herein, means that the concentration of the semi-solid hydrocarbons are preferably less than 10%, more preferably less than 5% most preferably less than 2% and even more preferably 0. Without being limited by theory, such semi-  
30 solid hydrocarbons tend to mask the sensory benefits of the siloxane elastomer compositions such as the non-greasy, light feel of the present invention.



Fatty acids and alcohols will have from 10 to 30 carbon atoms. Illustrative of this category are pelargonic, lauric, myristic, palmitic, stearic, isostearic, hydroxystearic, oleic, linoleic, ricinoleic, arachidic, behenic and erucic acids and alcohols.

Oily ester emollients may be those selected from one or more of the following classes:

- 5       1. Triglyceride esters such as vegetable and animal fats and oils. Examples include castor oil, safflower oil, cottonseed oil, corn oil, olive oil, cod liver oil, almond oil, avocado oil, palm oil, sesame oil, squalene, Kikui oil and soybean oil.
2. Acetoglyceride esters, such as acetylated monoglycerides.
3. Ethoxylated glycerides, such as ethoxylated glyceryl monostearate.
- 10       4. Alkyl esters of fatty acids having 10 to 20 carbon atoms. Methyl, isopropyl, and butyl esters of fatty acids are useful herein. Examples include hexyl laurate, isohexyl laurate, isohexyl palmitate, isopropyl palmitate, decyl oleate, isodecyl oleate, hexadecyl stearate, decyl stearate, isopropyl isostearate, diisopropyl adipate, diisohexyl adipate, dihexyldecyl adipate, diisopropyl sebacate, lauryl lactate, myristyl lactate, and cetyl lactate.
- 15       5. Alkenyl esters of fatty acids having 10 to 20 carbon atoms. Examples thereof include oleyl myristate, oleyl stearate, and oleyl oleate.
6. Ether-esters such as fatty acid esters of ethoxylated fatty alcohols.
7. Polyhydric alcohol esters. Ethylene glycol mono and di-fatty acid esters, diethylene glycol mono- and di-fatty acid esters, polyethylene glycol (200-6000) mono- and di-fatty acid  
20       esters, propylene glycol mono- and di-fatty acid esters, polypropylene glycol 2000 monooleate, polypropylene glycol 2000 monostearate, ethoxylated propylene glycol monostearate, glyceryl mono- and di-fatty acid esters, polyglycerol polyfatty esters, ethoxylated glyceryl monostearate, 1,2-butylene glycol monostearate, 1,2-butylene glycol distearate, polyoxyethylene polyol fatty acid ester, sorbitan fatty acid esters, and polyoxyethylene sorbitan fatty acid esters are  
25       satisfactory polyhydric alcohol esters.
8. Wax esters such as beeswax, spermaceti, myristyl myristate, stearyl stearate.
9. C1-C30 mono- and poly- esters of sugars and related materials. These esters are derived from a sugar or polyol moiety and one or more carboxylic acid moieties. Depending on the constituent acid and sugar, these esters can be in either liquid or solid form at room  
30       temperature. Examples of liquid esters include: glucose tetraoleate, the glucose tetraesters of soybean oil fatty acids (unsaturated), the mannose tetraesters of mixed soybean oil fatty acids, the galactose tetraesters of oleic acid, the arabinose tetraesters of linoleic acid, xylose tetralinoleate, galactose pentaoleate, sorbitol tetraoleate, the sorbitol hexaesters of unsaturated

soybean oil fatty acids, xylitol pentaoleate, sucrose tetraoleate, sucrose pentaoleate, sucrose hexaoleate, sucrose heptaoleate, sucrose octaoleate, and mixtures thereof. Examples of solid esters include: sorbitol hexaester in which the carboxylic acid ester moieties are palmitoleate and arachidate in a 1:2 molar ratio; the octaester of raffinose in which the carboxylic acid ester moieties are linoleate and behenate in a 1:3 molar ratio; the heptaester of maltose wherein the esterifying carboxylic acid moieties are sunflower seed oil fatty acids and lignocerate in a 3:4 molar ratio; the octaester of sucrose wherein the esterifying carboxylic acid moieties are oleate and behenate in a 1:3 molar ratio; and the octaester of sucrose wherein the esterifying carboxylic acid moieties are laurate, linoleate and behenate in a 1:3:4 molar ratio. A preferred solid material is sucrose polyester in which the degree of esterification is 7-8, and in which the fatty acid moieties are C18 mono- and/or di-unsaturated and behenic, in a molar ratio of unsaturates: behenic of 1:7 to 3:5. A particularly preferred solid sugar polyester is the octaester of sucrose in which there are about 7 behenic fatty acid moieties and about 1 oleic acid moiety in the molecule. Other materials include cottonseed oil or soybean oil fatty acid esters of sucrose. The ester materials are further described in, U.S. Patent 2,831,854, U.S. Patent 4,005,196, to Jandacek, issued Jan. 25, 1977; U.S. Patent 4,005,195, to Jandacek, issued Jan. 25, 1977, U.S. Patent 5,306,516, to Letton et al., issued Apr. 26, 1994; U.S. Patent 5,306,515, to Letton et al., issued Apr. 26, 1994; U.S. Patent 5,305,514, to Letton et al., issued Apr. 26, 1994; U.S. Patent 4,797,300, to Jandacek et al., issued Jan. 10, 1989; U.S. Patent 3,963,699, to Rizzi et al, issued Jun. 15, 1976; U.S. Patent 4,518,772, to Volpenhein, issued May 21, 1985; and U.S. Patent 4,517,360, to Volpenhein, issued May 21, 1985.

Amounts of the skin-conditioning agent may range from about 0% to 30%, preferably from about 1% to about 20%, optimally from about 1% to 10% by weight.

#### Solidifying Agent

The cosmetic compositions of this invention can contain one or more materials, herein singly or collectively referred to as a "solidifying agent", that are effective to solidify the particular liquid base materials to be used in a cosmetic composition. (As used herein, the term "solidify" refers to the physical and/or chemical alteration of the liquid base material so as to form a solid or semi-solid at ambient conditions, i.e., to form a final composition that has a stable physical structure and is deposited on the skin during normal use conditions.) As is appreciated by those skilled in the art, the selection of the particular solidifying agent for use in the cosmetic compositions will depend upon the particular type of composition desired, i.e., gel or wax-based, the desired rheology, the liquid base material used and the other materials to be used in the

composition. The solidifying agent is preferably present at a concentration of from about 0 to about 90%, more preferably from about 1 to about 50%, even more preferably from about 5% to about 40%, most preferably from about 1% to about 15%.

Suitable solidifying agents include waxy materials such as candelilla, carnauba waxes, beeswax, spermaceti, carnauba, baysberry, montan, ozokerite, ceresin, paraffin, synthetic waxes  
5 such as Fisher-Tropsch waxes, silicone waxes (e.g., DC 2503 from Dow Corning), microcrystalline waxes and the like; soaps, such as the sodium and potassium salts of higher fatty acids, i.e., acids having from 12 to 22 carbon atoms; amides of higher fatty acids; higher fatty acid amides of alkylolamines; dibenzaldehyde-monosorbitol acetals; alkali metal and alkaline  
10 earth metal salts of the acetates, propionates and lactates; and mixtures thereof. Also useful are polymeric materials such as, locust bean gum, sodium alginate, sodium caseinate, egg albumin, gelatin agar, carrageenin gum sodium alginate, xanthan gum, quince seed extract, tragacanth gum, starch, chemically modified starches and the like, semi-synthetic polymeric materials such as cellulose ethers (e.g. hydroxyethyl cellulose, methyl cellulose, hydroxypropyl cellulose,  
15 carboxymethyl cellulose, hydroxy propylmethyl cellulose), polyvinylpyrrolidone, polyvinylalcohol, guar gum, hydroxypropyl guar gum, soluble starch, cationic celluloses, cationic guar and the like and synthetic polymeric materials such as carboxyvinyl polymers, polyvinylpyrrolidone, polyvinyl alcohol polyacrylic acid polymers, polymethacrylic acid polymers, polyvinyl acetate polymers, polyvinyl chloride polymers, polyvinylidene chloride  
20 polymers and the like. Inorganic thickeners may also be used such as aluminum silicates, such as, for example, bentonites, or a mixture of polyethylene glycol and polyethylene glycol stearate or distearate. Naturally occurring polymers or biopolymers and their use are further described in European Application No. 522624, to Dunphy et al. Additional examples of naturally occurring polymers or biopolymers can be found in the Cosmetic Bench Reference, pp. 1.40-1.42, herein  
25 incorporated by reference.

Also useful herein are hydrophilic gelling agents such as the acrylic acid/ethyl acrylate copolymers and the carboxyvinyl polymers sold by the B.F. Goodrich Company under the trademark of Carbopol Registered TM resins. These resins consist essentially of a colloiddally water-soluble polyalkenyl polyether crosslinked polymer of acrylic acid crosslinked with from  
30 0.75% to 2.00% of a crosslinking agent such as polyallyl sucrose or polyallyl pentaerythritol. Examples include Carbopol 934, Carbopol 940, Carbopol 950, Carbopol 980, Carbopol 951 and Carbopol 981. Carbopol 934 is a water-soluble polymer of acrylic acid crosslinked with about 1% of a polyallyl ether of sucrose having an average of about 5.8 allyl groups for each sucrose

molecule. Also suitable for use herein are carbomers sold under the Trade Name "Carbopol Ultrez 10, Carbopol ETD2020, Carbopol 1382, Carbopol 1342 and Pemulen TR-1 (CTFA Designation: Acrylates/10-30 Alkyl Acrylate Crosspolymer). Combinations of the above polymers are also useful herein. Other gelling agents suitable for use herein include oleogels such as trihydroxystearin.

Hydrophobically modified celluloses are also suitable for use herein. These celluloses are described in detail in U.S. Patents 4,228,277 and 5,104,646, both of which are herein incorporated by reference in their entirety.

Additional examples of suitable gelling agents or gellants can be found in the Cosmetic Bench Reference, p. 1.27, herein incorporated by reference.

Further examples of suitable solidifying agents disclosed in the following references, all of which are incorporated by reference herein: U.S. Patent 4,151,272, Geary, et al., issued Apr. 24, 1979; U.S. Patent 4,229,432, Geria, issued Oct. 21, 1980; and U.S. Patent 4,280,994, Turney, issued July 28, 1981; "The Chemistry and Technology of Waxes", A. H. Warth, 2nd Edition, reprinted in 1960, Reinhold Publishing Corporation, pp 391-393 and 421; "The Petroleum Chemicals Industry", R. F. Goldstein and A. L. Waddeam, 3rd Edition (1967), E & F. N. Span Ltd., pp 33-40; "The Chemistry and Manufacture of Cosmetics", M. G. DeNavarre, 2nd edition (1970), Van Nostrand & Company, pp 354-376; and in "Encyclopedia of Chemical Technology", Vol. 24, Kirk-Othmer, 3rd Edition (1979) pp 466-481; U.S. Patent 4,126,679, Davy, et al., issued Nov. 21, 1978; European Patent Specification No. 117,070, May, published Aug. 29, 1984; U.S. Patent 2,900,306, Slater, issued Aug. 18, 1959; U.S. Patent 3,255,082, Barton, issued June 7, 1966; U.S. Patent 4,137,306, Rubino, et al., issued Jan. 30, 1979; U.S. Patent 4,154,816, Roehl, et al., issued May 15, 1979; U.S. Patent 4,226,889, Yuhua, issued Oct. 7, 1980; U.S. Patent 4,346,079, Roehl, issued Aug. 24, 1982; U.S. Patent 4,383,988, Teng, et al., issued May 17, 1983; European Patent Specification No. 107,330, Luebbe, et al., published May 2, 1984; European Patent Specification No. 24,365 Sampson, et al., published Mar. 4, 1981; and U.S. patent application Ser. No. 630,790, DiPietro, filed July 13, 1984.

Preferably, the compositions of the present invention have a hardness value as measured using a TA-XT2i Texture Analyzer (described below) of up to about 25 gram-force, more preferably from about 0.5 to about 20 gram-force, most preferably from about 1 to about 15, optimally from about 1 to about 10 gram-force. Without being limited by theory, it is believed that compositions having stick hardness values above 25 gram-force tend to interfere with the formation of the film structure provided by the polysiloxane elastomer, thus, preventing the

smoothness as well as improved uniformity and evenness of particle distribution within the film. This, in turn, negatively affects the sensory benefits of the cross-linked polysiloxane elastomer component.

#### Colorants

5           Certain embodiments of the present invention contain from about 0% to about 30%, preferably from about 1% to about 20%, more preferably from about 2% to about 15% and most preferably from about 5% to about 15%, of a colorant, on an anhydrous pigment weight basis. These are usually aluminum, barium or calcium salts or lakes. Preferably, dyes are present at from about 0% to about 3% and pearls and the like from 0% to about 10%.

10           Colorants useful herein are all inorganic and organic colors/pigments suitable for use in cosmetic compositions. When used, pigments are typically dispersed in emollients for the good dispersion of the pigments when incorporated into lip compositions of the present invention, thus providing an even distribution of color.

          Lakes are either a pigment that is extended or reduced with a solid diluent or an organic pigment that is prepared by the precipitation of a water-soluble dye on an adsorptive surface, which usually is aluminum hydrate. There is uncertainty in some instances as to whether the soluble dye precipitates on the surface of the aluminum hydrate to yield a dyed inorganic pigment or whether it merely precipitates in the presence of the substrate. A lake also forms from precipitation of an insoluble salt from an acid or basic dye. Calcium and barium lakes are also  
15           used herein.

          Lakes suitable for use in the present invention include Red 3 Aluminum Lake, Red 21 Aluminum Lake, Red 27 Aluminum Lake, Red 28 Aluminum Lake, Red 33 Aluminum Lake, Yellow 5 Aluminum Lake, Yellow 6 Aluminum Lake, Yellow 10 Aluminum Lake, Orange 5 Aluminum Lake and Blue 1 Aluminum Lake, Red 6 Barium Lake, Red 7 Calcium Lake.

25           Other colors can also be included in the lipsticks, such as dyes. Suitable examples include Red 6, Red 21, Brown, Russet and Sienna dyes and mixtures thereof.

          There are no specific limitations as to the pigment, colorant or filler powders used in the composition. Each may be a body pigment, inorganic white pigment, inorganic colored pigment, pearling agent, and the like. Specific examples are talc, mica, magnesium carbonate, calcium carbonate, magnesium silicate, aluminum magnesium silicate, silica, titanium dioxide, zinc oxide,  
30           red iron oxide, yellow iron oxide, black iron oxide, ultramarine, polyethylene powder, methacrylate powder, polystyrene powder, silk powder, crystalline cellulose, starch, titanated mica, iron oxide titanated mica, bismuth oxychloride, and the like.

Additional pigment/powder fillers include, but are not limited to, inorganic powders such as gums, chalk, Fuller's earth, kaolin, sericite, muscovite, phlogopite, synthetic mica, lepidolite, biotite, lithia mica, vermiculite, aluminum silicate, starch, smectite clays, alkyl and/or trialkyl aryl ammonium smectites, chemically modified magnesium aluminum silicate, organically modified montmorillonite clay, hydrated aluminum silicate, fumed aluminum starch octenyl succinate barium silicate, calcium silicate, magnesium silicate, strontium silicate, metal tungstate, magnesium, silica alumina, zeolite, barium sulfate, calcined calcium sulfate (calcined gypsum), calcium phosphate, fluorine apatite, hydroxyapatite, ceramic powder, metallic soap (zinc stearate, magnesium stearate, zinc myristate, calcium palmitate, and aluminum stearate), colloidal silicone dioxide, and boron nitride; organic powder such as polyamide resin powder (nylon powder), cyclodextrin, methyl polymethacrylate powder, copolymer powder of styrene and acrylic acid, benzoguanamine resin powder, poly(ethylene tetrafluoride) powder, and carboxyvinyl polymer, cellulose powder such as hydroxyethyl cellulose and sodium carboxymethyl cellulose, ethylene glycol monostearate; inorganic white pigments such as magnesium oxide. Other useful powders are disclosed in U.S. Patent 5, 688,831, to El-Nokaly et al., issued November 18, 1997, herein incorporated by reference in its entirety. These pigments and powders can be used independently or in combination.

Also useful herein are pigment and/or dye encapsulates such nanocolorants from BASF and multi-layer interference pigments such as Sicopearls from BASF.

It is preferred that the pigments/powders are surface treated to provide added stability of color and ease of formulation. Hydrophobically treated pigments are more preferred, because they may be more easily dispersed in the solvent/oil phase. In addition, it may be useful to treat the pigments with a material that is compatible with a silicone phase. Particularly useful hydrophobic pigment treatments for use in water-in-silicone emulsions include polysiloxane treatments such as those disclosed in U.S. Patent 5,143,722, incorporated herein by reference in its entirety. Also preferred are pigment/powders having a primary average particle size of from about 5 nm to about 100,000 nm, more preferably from about 50nm to about 5,000nm, most preferably from about 100nm to about 1000nm. Mixtures of the same or different pigment/powder having different particle sizes are also useful herein (e.g., incorporating a TiO<sub>2</sub> having a primary particle size of from about 100 nm to about 400 nm with a TiO<sub>2</sub> having a primary particle size of from about 10 nm to about 50 nm).

Dispersants may also be used in conjunction with the colors and pigments of the present invention. Examples of suitable dispersants include, but are not limited to, those described in U.S. Patent 5,688,493, herein incorporated by reference in its entirety.

#### Preservatives

5           Suitable traditional preservatives for compositions of this invention are alkyl esters of para-hydroxybenzoic acid. Other preservatives that have more recently come into use include hydantoin derivatives such as 1,3-bis (hydroxymethyl)-5,5-dimethylhydantoin, propionate salts, and a variety of quaternary ammonium compounds such as benzalkonium chloride, quaternium 15 (Dowicil 200), benzethonium Chloride, and methylbenzethonium chloride. Cosmetic chemists  
10 are familiar with appropriate preservatives and routinely choose them to satisfy the preservative challenge test and to provide product stability. Particularly preferred preservatives are disodium EDTA, phenoxyethanol, methyl paraben, propyl paraben, imidazolidinyl urea (commercially available as Germall 1157), sodium dehydroacetate and benzyl alcohol. The preservatives should  
15 be selected having regard for the use of the composition and possible incompatibilities between the preservatives and other ingredients in the emulsion. Preservatives preferably are employed in amounts ranging from about 0% to about 5%, more preferably from about 0.01% to about 2.5%, and most preferably from about 0.01% to about 1%, by weight of the composition.

#### Emulsifiers

          Emulsifiers or surfactants can also be used herein. These emulsifiers may be nonionic,  
20 anionic or cationic. Suitable emulsifiers are disclosed in, for example, U.S. Patent 3,755,560, issued Aug. 28, 1973, Dickert et al.; U.S. Patent 4,421,769, issued Dec. 20, 1983, Dixon et al.; and McCutcheon's Detergents and Emulsifiers, North American Edition, pages 317-324 (1986), each incorporated herein by reference in its entirety. Illustrative nonionic surfactants are alkoxylated compounds based on C10-C22 fatty alcohols and acids, and sorbitan. These  
25 materials are available, for instance, from the Shell Chemical Company under the Neodol trademark, Copolymers of polyoxypropylene-polyoxyethylene, sold by the BASF Corporation under the Pluronic trademark, are sometimes also useful. Alkyl polyglycosides available from the Henkel Corporation may also be utilized for purposes of this invention. Anionic type emulsifiers or surfactants include fatty acid soaps, sodium lauryl sulphate, sodium lauryl ether sulphate, alkyl  
30 benzene sulphonate, mono- and di-alkyl acid phosphates and sodium fatty acyl isethionate. Amphoteric emulsifiers or surfactants include such materials as dialkylamine oxide and various types of betaines (such as cocamidopropyl betaine).

Preferred for use herein are polyoxyalkylene copolymers also known as silicone polyethers. Polymers are described in detail in U. S. Patent 4,268,499, which is incorporated herein by reference in its entirety. A particularly preferred polyoxyalkylene copolymer is known by its CTFA designation as dimethicones copolyol. A particularly preferred form of dimethicone  
5 copolyol is that supplied by Dow Corning as DC5225C.

The overall concentration of the emulsifier can be from 0% to about 10% of the formulation, preferably from 0.1% to about 5% and most preferably from about 0.1% to about 2%, by weight of the composition. Examples of suitable emulsifiers can be found in U.S. Patent 5,085,856 to Dunphy et al.; Japanese Patent Publication Sho 61-83110; European Patent  
10 Application EP 522624 to Dunphy et al.; U.S. patent 5,688,831 to El-Nokaly et al.; and Examples of suitable moistures can be found in Cosmetic Bench Reference, pp. 1.22, 1.24-1.26 (1996), all of which are herein incorporated by reference in their entirety.

#### Essentially Anhydrous

Cosmetic compositions of the present invention are essentially anhydrous. The amount  
15 of water will be confined to range from 0 to 5%, preferably not above 4%, more preferably not above 2%, optimally not above 0.5% by weight.

#### Organic Sunscreens

Compositions of the present invention preferably comprise an organic sunscreen. Suitable sunscreens can have UVA absorbing properties, UVB absorbing properties or a mixture  
20 thereof. The exact amount of the sunscreen active will vary depending upon the desired Sun Protection Factor, i.e. the "SPF" of the composition as well as the desired level of UVA protection. The compositions of the present invention preferably comprise an SPF of at least 10, preferably at least 15. (SPF is a commonly used measure of photoprotection of a sunscreen against erythema. The SPF is defined as a ratio of the ultraviolet energy required to produce  
25 minimal erythema on protected skin to that required to products the same minimal erythema on unprotected skin in the same individual. See Federal Register, 43, No 166, pp. 38206-38269, August 25, 1978). Compositions of the present invention preferably comprise from about 2% to about 20%, more typically from about 4% to about 14%, by weight, of organic sunscreen. Suitable sunscreens include, but are not limited to, those found in the *CTFA International*  
30 *Cosmetic Ingredient Dictionary and Handbook*, 7<sup>th</sup> edition, volume 2 pp. 1672, edited by Wenninger and McEwen (*The Cosmetic, Toiletry, and Fragrance Association, Inc., Washington, D. C., 1997*).



The compositions of the present invention preferably comprise a UVA absorbing sunscreen actives that absorb UV radiation having a wavelength of from about 320nm to about 400nm. Suitable UVA absorbing sunscreen actives are selected from dibenzoylmethane derivatives, anthranilate derivatives such as methylantranilate and homomethyl, 1-N-acetylantranilate, and mixtures thereof. Examples of dibenzoylmethane sunscreen actives are described in US Patent No 4,387,089 issued to Depolo; and in Sunscreens: Development, Evaluation, and Regulatory Aspects edited by N. J. Lowe and N. A. Shaath, Marcel Dekker, Inc (1990). The UVA absorbing sunscreen active is preferably present in an amount to provide broad-spectrum UVA protection either independently, or in combination with, other UV protective actives that may be present in the composition.

Preferred UVA sunscreen actives are dibenzoylmethane sunscreen actives and their derivatives. They include, but are not limited to, those selected from 2-methyldibenzoylmethane, 4-methyldibenzoylmethane, 4-isopropyldibenzoylmethane, 4-tert-butyldibenzoylmethane, 2, 4-dimethyldibenzoylmethane, 2, 5-dimethyldibenzoylmethane, 4, 4'-diisopropylbenzoylmethane, 4-(1, 1-dimethylethyl)-4'-methoxydibenzoylmethane, 2-methyl-5-isopropyl-4'-methoxydibenzoylmethane, 2-methyl-5-tert-butyl-4'-methoxy-dibenzoylmethane, 2, 4-dimethyl-4'-methoxydibenzoylmethane, 2, 6-dimethyl-4'-tert-butyl-4'-methoxydibenzoylmethane, and mixtures thereof. Preferred dibenzoyl sunscreen actives include those selected from 4-(1, 1-dimethylethyl)-4'-methoxydibenzoylmethane, 4-isopropyldibenzoylmethane, and mixtures thereof. A more preferred sunscreen active is 4-(1, 1-dimethylethyl)-4'-methoxydibenzoylmethane.

The sunscreen active 4-(1, 1-dimethylethyl)-4'-methoxydibenzoylmethane, which is also known as butyl methoxydibenzoylmethane or Avobenzone, is commercially available under the names of Parsol® 1789 from Givaudan Roure (International) S. A. (Basel, Switzerland) and Eusolex® 9020 from Merck & Co., Inc (Whitehouse Station, NJ). The sunscreen 4-isopropyldibenzoylmethane, which is also known as isopropyldibenzoylmethane, is commercially available from Merck under the name of Eusolex® 8020.

The compositions of the present invention preferably further comprise a UVB sunscreen active that absorbs UV radiation having a wavelength of from about 290nm to about 320nm. The compositions preferably comprise an amount of the UVB sunscreen active that is safe and effective to provide UVB protection either independently, or in combination with, other UV protective actives that may be present in the compositions. The compositions preferably

comprise from about 0.1% to about 16%, more preferably from about 0.1% to about 12%, and most preferably from about 0.5% to about 8% by weight, of UVB absorbing organic sunscreen.

A wide variety of UVB sunscreen actives are suitable for use herein. Nonlimiting examples of such organic sunscreen actives are described in US Patent No 5,087,372 issued February 11, 1992 to Haffey et al.; and US Patent Nos 5,073,371 and 5,073,372 both issued on December 17, 1991 to Turner et al.. Preferred UVB sunscreen actives are selected from 2-ethylhexyl-2-cyano-3, 3-diphenylacrylate (referred to as octocrylene), 2-phenyl-benzimidazole-5-sulphonic acid (PBSA), cinnamates and their derivatives such as 2-ethylhexyl-p-methoxycinnamate and octyl-p-methoxycinnamate, TEA salicylate, octyldimethyl PABA, camphor derivatives and their derivatives, and mixtures thereof. Preferred organic sunscreen actives are 2-ethylhexyl-2-cyano-3, 3-diphenylacrylate (referred to as octocrylene), 2-phenyl-benzimidazole-5-sulphonic acid (PBSA), octyl-p-methoxycinnamate, and mixtures thereof. Salt and acid neutralised forms of the acidic sunscreens are also useful herein. When organic sunscreen salts, such as PBSA, are used within compositions of the present invention they can disrupt the action of the thickener with the result that the final product may have sub optimal rheology. This can be countered by the addition of higher levels of thickener, fatty alcohols or nonionic surfactants such that the rheology of the final product returns to the desired level.

An agent may also be added to any of the compositions useful in the present invention to stabilise the UVA sunscreen to prevent it from photo-degrading on exposure to UV radiation and thereby maintaining its UVA protection efficacy. Wide ranges of compounds have been cited as providing these stabilising properties and should be chosen to compliment both the UVA sunscreen and the composition as a whole. Suitable stabilising agents include, but are not limited to, those described in US Patents Nos 5,972,316; 5,968,485; 5,935,556; 5,827,508 and Patent WO 00/06110. Preferred examples of stabilising agents for use in the present invention include 2-ethylhexyl-2-cyano-3, 3-diphenylacrylate (referred to as octocrylene), ethyl-2-cyano-3, 3-diphenylacrylate, 2-ethylhexyl-3, 3-diphenylacrylate, ethyl-3, 3-bis (4-methoxyphenyl) acrylate, and mixtures thereof. 2-ethylhexyl-2-cyano-3, 3-diphenylacrylate is most preferred.

An agent may also be added to any of the compositions useful in the present invention to improve the skin substantivity of those compositions, particularly to enhance their resistance to being washed off by water, or rubbed off. A preferred agent that will provide this benefit is a copolymer of ethylene and acrylic acid. Compositions comprising this copolymer are disclosed in U.S. Patent 4,663,157, Brock, issued May 5, 1987.

#### Inorganic Sunscreens

In addition to the organic sunscreens compositions of the present invention can additionally comprise inorganic physical sunblocks. Nonlimiting examples of suitable physical sunblocks are described in CTFA International Cosmetic Ingredient Dictionary, 6<sup>th</sup> Edition, 1995, pp. 1026-28 and 1103, Sayre, R. M. et al., "Physical Sunscreens", J. Soc. Cosmet. Chem., Vol 41, no 2, pp. 103-109 (1990). Preferred inorganic physical sunblocks are zinc oxide and titanium dioxide, and mixtures thereof.

When used, the physical sunblocks are present in an amount such that the present compositions are transparent on the skin (i.e. non-whitening), preferably less than or equal to about 5%. When titanium dioxide is used, it can have an anatase, rutile, or amorphous structure. Physical sunblock particles, e.g. titanium dioxide and zinc oxide, can be uncoated or coated with a variety of materials including but not limited to amino acids, aluminum compounds such as alumina, aluminum stearate, aluminum laurate, and the like; carboxylic acids and their salts e.g. stearic acid and its salts; phospholipids such as lecithin; organic silicone compounds; inorganic silicone compounds such as silica and silicates; and mixtures thereof. A preferred titanium dioxide is commercially available from Tayca (Japan) and is distributed by Tri-K Industries (Emerson, NJ) under the MT micro-ionized series (e.g. MT 100SAS).

The compositions of the present invention preferably comprise from about 0.1% to about 10%, more preferably from about 0.1% to about 4%, and most preferably from about 0.5% to about 2.5%, by weight, of inorganic sunscreen.

#### Aerated Compositions

Optionally and preferably, the compositions of the present invention are aerated. By "aerated" as used herein means the air is incorporated either by hand, mechanical mixing or by using any other form of conventional foaming or whipping instrument technology. Preferably the compositions of the present invention contain at least about 1%, preferably at least about 2%, optimally from about 3 to about 5% air.

#### Other Optional Ingredients

A variety of additional ingredients can be incorporated into the compositions of the present invention. Nonlimiting examples of these additional ingredients include additional skin care actives such as peptides (e.g., Matrixyl [pentapeptide derivative]), farnesol, bisabolol, phytantriol, glycerol, urea, guanidine (e.g., amino guanidine); vitamins and derivatives thereof such as ascorbic acid, vitamin A (e.g., retinoid derivatives such as retinyl palmitate or retinyl propionate), vitamin E (e.g., tocopherol acetate), vitamin B<sub>3</sub> (e.g., niacinamide) and vitamin B<sub>5</sub> (e.g., panthenol) and the like and mixtures thereof; sunscreens; anti-acne medicaments

(resorcinol, salicylic acid, and the like; antioxidants (e.g., phytosterols, lipoic acid); flavonoids (e.g., isoflavones, phytoestrogens); skin soothing and healing agents such as aloe vera extract, allantoin and the like; chelators and sequestrants; and agents suitable for aesthetic purposes such as essential oils, fragrances, skin sensates, opacifiers, aromatic compounds (e.g., clove oil, menthol, camphor, eucalyptus oil, and eugenol). Nonlimiting examples of suitable carboxylic copolymers, emulsifiers, emollients, and other additional ingredients are disclosed in U.S. Patent 5,011,681, to Ciotti et al., issued April 30, 1991 and US Patent 5,939,082, to Oblong et al., issued August 17, 1999, both of which are herein incorporated by reference. The above-mentioned vitamin B<sub>3</sub> compounds can be incorporated as re-crystallized crystals that remain in crystalized form in the composition or as partially solubilize crystals (i.e., some of the crystals are dissolved and some remain in crystalline form in the composition.).

#### Analytical Test Methods

##### Hardness Value Test

The term "product hardness" as used herein is a reflection of how much force is required to move a rod a specified distance and at a controlled rate into a cosmetic composition under the following test conditions. Higher values represent harder product, and lower values represent softer product. These values are measured at 27°C, 15% relative humidity, using a TA-XT2i Texture Analyzer, available from Texture Technology Corp., Scarsdale, New York, U.S.A. The product hardness value as used herein represents the amount of force required to move a 16mm long stainless steel rod having a 0.254mm diameter through the composition for a distance of 12.2mm at a rate of 0.85mm/second. The rod is attached to the instrument by means of a suitable adapter (e.g., drill-type chuck). Other test parameters include: Pre-Test Speed of 0.85 mm/s, Post Test Speed of 1.70 mm/s, trigger distance of 0.1mm. More detailed instructions can be found in the Operator's Manual for the TA-XT2i, herein incorporated by reference.

#### ASSOCIATED METHODS

Applicants have found that the compositions of the present invention are useful in a variety of applications directed to enhancement of mammalian skin. The methods of use for the compositions disclosed and claimed herein include, but are not limited to: 1) methods of increasing the substantivity of a cosmetic to skin; 2) methods of moisturizing skin; 3) methods of improving the natural appearance of skin; 4) methods of applying a color cosmetic to skin; 5) methods of preventing, retarding, and/or treating wrinkles; 6) methods of providing UV protection to skin; 7) methods of preventing, retarding, and/or controlling the appearance of oil; 8) methods of modifying the feel and texture of skin; 9) methods of providing even skin tone; 10)

methods of preventing, retarding, and/or treating the appear of spider vessels and varicose veins; 11) methods of masking the appearance of vellus hair on skin; and 12) methods of concealing blemishes and/or imperfections in human skin, including acne, age spots, freckles, moles, scars, under eye circles, birth marks, post-inflammatory hyperpigmentation, etc.. Each of the methods discussed herein involve topical application of the claimed compositions to skin.

The following examples will more fully illustrate the embodiments of this invention. All parts, percentages and proportions referred to herein and in the appended claims are by weight unless otherwise indicated.

### EXAMPLES

The cosmetic products in the following examples illustrate specific embodiments of the cosmetic compositions of the present invention, but are not intended to be limiting thereof. The skilled artisan can undertake other modifications without departing from the spirit and scope of this invention. All exemplified compositions can be prepared by conventional formulation and mixing techniques. Component amounts are listed as weight percents and may exclude minor materials such as diluents, filler, and so forth. The listed formulations, therefore, comprise the listed components and any minor materials associated with such components.

#### Example I

A foundation compact of the present invention comprising cross-linked siloxane elastomer is prepared as follows:

<u>Ingredient</u>	<u>Wt %</u>
TiO <sub>2</sub> silicone treated (SAT treated Tronox CR 837 supplied US Cosmetics)	5.25
Pigment	1.23
Talc (silicone treated) (Hydrophobic Talc 9742 supplied by Warner Jenkinson)	2.36
TiO <sub>2</sub> -MT100T (micronized TiO <sub>2</sub> supplied by Tri-K)	0.16
DC245 (cyclomethicone)	16.34
DC5225C (dimethicone copolyol - 10% active)	0.31
KSG21 Elastomer Gel <sup>1</sup>	48.00
propylparaben (preservative)	0.10
Glycerine	20.00

Ozokerite Wax	6.25
Total	100.00

<sup>1</sup> 25% Dimethicone/Copolyol Crosspolymer in dimethicone

In a suitable vessel equipped with a heating source, the pigments, TiO<sub>2</sub> (micronized and silicone treated), hydrophobic talc, KSG21, cyclomethicone (DC245) and dimethicone copolyol (DC5225C) are mixed until homogeneous and then milled using a Silverson L4RT mixer at 9000  
5 rpms to the desired particle size. Next, the propylparaben and glycerine are added to the above mixture and mixed until homogenous. The mixture is then heated to a temperature of between 85 - 90°C, at which time the ozokerite wax is added (melted into the mixture) with mixing until the mixture homogenous. The mixture is then poured into a mold and allowed to cool at room  
10 temperature. Once cooled, the mixture incorporated into the appropriate package.

The foundation compact is applied to the face to provide color, moisturization and improved feel.

#### Example II

A mousse foundation of the present invention comprising cross-linked siloxane elastomer  
15 is prepared as follows:

<u>Ingredient</u>	<u>Wt %</u>
TiO <sub>2</sub> silicone treated (SAT treated Tronox CR 840 supplied US Cosmetics)	8.45
Pigment	2.00
Talc- Silicone Treated	3.84
TiO <sub>2</sub> -MT100T (micronized)	0.26
DC245 (cyclomethicone)	7.65
DC5225C (Dimethicone Copolyol)	0.50
KSG21 Elastomer Gel <sup>1</sup>	52.1
propylparaben (preservative)	0.10
Glycerin	25.00
Methylparaben (preservative)	0.10
TOTAL	100.00

<sup>1</sup> 25% Dimethicone/Copolyol Crosspolymer in dimethicone

In a suitable vessel, methylparaben is added to the glycerin and mixed until dissolved. Then the pigments, TiO<sub>2</sub> (micronized and silicone treated), hydrophobic talc, KSG21, cyclomethicone (DC245) and dimethicone copolyol (DC5225C) are mixed until homogeneous and, then, milled using a Silverson L4RT mixer at 9000 rpms to the desired particle size. Next, the propylparaben is added to the above mixture and mixed until homogenous. The mixture is, then, incorporated into the appropriate package.

The foundation is applied to the face to provide color, moisturization and improved feel.

#### Example III

A lip gel of the present invention comprising cross-linked siloxane elastomer is prepared as follows:

<u>Ingredient</u>	<u>Wt %</u>
KSG 21 Elastomer Gel <sup>1</sup>	55.00
Cyclomethicone (DC245 fluid)	6.80
Dimethicone Fluid (DC200 fluid) 50 cst	4.50
Glycerine	25.00
Pigment	8.50
Preservative	0.20
TOTAL	100.0

<sup>1</sup> 25%Dimethicone/Copolyol Crosspolymer in dimethicone

In a suitable vessel, all the ingredients combined and mixed until homogeneous using conventional mixing technology. The mixture is, then, incorporated into the appropriate package.

The lip gel is applied to the lips to provide color, moisturization and improved feel.

#### Example IV

A lip balm of the present invention comprising cross-linked siloxane elastomer is prepared as follows:

<u>Ingredient</u>	<u>Wt%</u>
Stearyl Dimethicone (DC 2503 wax)	10.00
Glycerine	30.00

KSG21 Elastomer Gel <sup>1</sup>	46.15
Cyclomethicone (DC-245)	1.55
Dimethicone copolyol (DC-5225C)	5.00
Preservative	0.30
Ozokerite wax	7.00
TOTAL	100.0

<sup>1</sup> 25%Dimethicone/Copolyol Crosspolymer in dimethicone

In a suitable vessel equipped with a heating source, the stearyl dimethicone, glycerine, KSG21, cyclomethicone, dimethicone copolyol, and preservative are added and mixed using a Caframo RZR50 mixer at 100 to 300 rpms until homogeneous. The mixture is then heated to a temperature of between 85 - 90°C, at which time the ozokerite wax is added (melted into the mixture) with mixing until the mixture is homogenous. The mixture is then poured into a mold and allowed to cool at room temperature. The mixture is cooled to ambient temperature and incorporated into the appropriate package.

The lip balm is applied to the lips to provide moisturization and improved feel.

10

#### Example V

A wrinkle hiding gel of the present invention comprising cross-linked siloxane elastomer is prepared as follows:

<u>Ingredient</u>	<u>Wt%</u>
DC 9011 Elastomer Gel <sup>1</sup>	59.7
Glycerin	25
Preservative	0.3
Ethylene/Acrylic Acid Copolymer (Flowbead EA-209)	15.0
TOTAL	100.0

<sup>1</sup> 25%Dimethicone/Copolyol Crosspolymer in dimethicone

15 In a suitable vessel, the elastomer gel, glycerine, preservative and ethylene/acrylic acid copolymer are mixed using a Caframo RZR50 mixer at 100 to 300 rpms until homogeneous. The mixture is, then, incorporated into the appropriate package.

The wrinkle hiding gel is applied to the face to provide moisturization, improved skin feel and conceal wrinkles.



Examples VI - XIV

Cream foundations suitable for application to the face to reduce the appearance of oily shine are made as follows.

<u>Ingredient</u>	<u>VI</u>	<u>VII</u>	<u>VIII</u>	<u>IX</u>	<u>X</u>	<u>XI</u>	<u>XII</u>	<u>XIII</u>	<u>XIV</u>
KSG 21 Elastomer Gel	20.00	30.00	27.53	50.00	50.00	32.53	30.00	25.00	35.00
Cyclopentasiloxane	6.53	9.25	2.00	2.75	6.75	5.00	4.75	9.03	2.75
Isoeicosane	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00
Vitamin E Acetate	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50
<b>Particulates</b>									
Ethylene & Acrylic Acid Copolymer microspheres (EA209)	10.00	10.00	10.00	5.00	5.00	10.00	10.00	10.00	10.00
Silica and Titanium Dioxide and Iron Oxides (Ronasphere LDP)	2.00	-	-	5.00	2.00	5.00	5.00	5.00	5.00
Silica	3.00	3.00	2.00	-	-	-	-	-	-
Magnesium Aluminum Silicate	-	2.00	-	-	-	-	-	-	-
Allyl methacrylates copolymer	3.00		3.00		-	2.00	2.00	2.00	2.00
Acrylates copolymer	1.00	-	-	2.00	-	3.00	3.00	3.00	3.00
Nylon 12		5.00	1.00	-	2.00	-	-	-	-
Aluminum Starch Succinate	1.00	2.00	-	-	-	1.00	2.00	3.00	4.00
Treated powders*	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
<b>Film forming agents</b>									
Polysilicone 7	17.00	-	17.00	-	-	-	-	-	-
Pressure Sensitive Adhesive	-	-	-	-	3.00	-	-	-	-
Silicone Resin	-	-	-	-	-	-	5.00	5.00	5.00
<b>Solidifying agents</b>									
Ozokerite	2.00	2.00	-	-	-	-	-	-	-

Stearyl Dimethicone	-	-	-	2.00	-	-	-	-	-
<b>Humectants &amp; skin-conditioning agents</b>									
Glycerin	20.00	25.00	20.00	25.00	20.00	25.00	25.00	20.00	20.00
Niacinamide	2.00	3.50	5.00	-	2.00	3.50	5.00	5.00	5.00
Panthenol	0.50	1.00	0.50	1.00	2.00	1.00	1.00	1.00	1.00
<b>Preservatives</b>									
Disodium EDTA	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
Methyl Paraben	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
Benzyl Alcohol	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
Propyl Paraben	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
Ethyl Paraben	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
<b>Sunscreens</b>									
Butyl Methoxydibenzoyl methane	2.00	-	2.00	-	-	2.00	-	2.00	-
Octyl Salicylate	0.50	-	0.50	-	-	0.50	-	0.50	-
Octocrylene	1.00	-	1.00	-	-	1.00	-	1.00	-
Phenylbenzimidazole Sulphonic Acid	0.60	-	0.60	-	-	0.60	-	0.60	-
Triethanolamine	0.62	-	0.62	-	-	0.62	-	0.62	-
<b>Total</b>	<b>100.00</b>	<b>100.00</b>	<b>100.00</b>	<b>100.00</b>	<b>100.00</b>	<b>100.00</b>	<b>100.00</b>	<b>100.00</b>	<b>100.00</b>

\*= Mixture of iron oxides and titanium dioxides

- In a suitable vessel equipped with a heating source, KSG21, cyclopentasiloxane, Isoleicosane, Vitamin E Acetate (DC245) and film formers are mixed until homogeneous. Next, the preservatives and glycerine and skin conditioning agents are added to the above mixture and mixed until homogenous. The mixture is then heated to a temperature of between 85 - 90°C, at which time the solidifying agent (if used) is added (melted into the mixture) with mixing until the mixture homogenous. Add the particulate materials to the mixture and mix until homogeneous. The mixture is then cooled to room temperature. Once cooled, the mixture incorporated into the appropriate package.

Examples XV - XXII

Cream foundations suitable for application to the face to reduce the appearance of oily shine are made as follows. The foundations provide color, moisturization and improved feel.

<u>Ingredient</u>	<u>XV</u>	<u>XVI</u>	<u>XVI</u>	<u>XVII</u>	<u>XVIII</u>	<u>XIX</u>	<u>XX</u>	<u>XXI</u>	<u>XXII</u>
KSG 21 Elastomer Gel	20.00	30.00	27.53	50.00	50.00	32.53	30.00	25.00	35.00
Cyclopentasiloxane	5.86	8.58	1.33	2.08	3.08	4.33	4.08	8.36	2.08
Isoeicosane	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00
Vitamin E Acetate	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50
Particulates									
Silica and Titanium Dioxide and Iron Oxides (Ronasphere LDP)	2.00	-	-	0.00	0.00	5.00	5.00	5.00	5.00
Silica	3.00	3.00	2.00	-	-	-	-	-	-
Magnesium Aluminum Silicate	-	2.00	-	-	-	-	-	-	-
Allyl methacrylates copolymer	3.00		3.00		-	2.00	2.00	2.00	2.00
Acrylates copolymer	1.00	-	-	2.00	-	3.00	3.00	3.00	3.00
Nylon 12		5.00	1.00	-	2.00	-	-	-	-
Aluminum Starch Succinate	1.00	2.00	-	-	-	1.00	2.00	3.00	4.00
Titanium Dioxide	8.25	8.25	8.25	8.25	8.25	8.25	8.25	8.25	8.25
Yellow Iron Oxide	2.41	2.41	2.41	2.41	2.41	2.41	2.41	2.41	2.41
Red Iron Oxide	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89
Black Iron Oxide	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12	0.12
Film formers									
Polysilicone 7	17.00	-	17.00	-	-	-	-	-	-

Pressure Sensitive Adhesive	-	-	-	-	3.00	-	-	-	-
Silicone Resin	-	-	-	-	-	-	5.00	5.00	5.00
Solidifying agents									
Ozokerite	2.00	2.00	-	2.00	-	-	-	-	-
Glycerin	20.00	25.00	20.00	25.00	20.00	25.00	25.00	20.00	20.00
Niacinamide	2.00	3.50	5.00	-	2.00	3.50	5.00	5.00	5.00
Panthenol	0.50	1.00	0.50	1.00	2.00	1.00	1.00	1.00	1.00
Preservatives									
Disodium EDTA	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
Methyl Paraben	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
Benzyl Alcohol	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
Propyl Paraben	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10	0.10
Ethyl Paraben	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Sunscreens									
Butyl Methoxydibenzoyl methane	2.00	-	2.00	-	-	2.00	-	2.00	-
Octyl Salicylate	0.50	-	0.50	-	-	0.50	-	0.50	-
Octocrylene	1.00	-	1.00	-	-	1.00	-	1.00	-
Phenylbenzimidazole Sulphonic Acid	0.60	-	0.60	-	-	0.60	-	0.60	-
Triethanolamine	0.62	-	0.62	-	-	0.62	-	0.62	-
<b>Total</b>	<b>100.00</b>	<b>100.00</b>	<b>100.00</b>	<b>100.00</b>	<b>100.00</b>	<b>100.00</b>	<b>100.00</b>	<b>100.00</b>	<b>100.00</b>

In a suitable vessel equipped with a heating source, the pigments, TiO<sub>2</sub> (micronized and silicone treated), hydrophobic talc, KSG21, cyclomethicone (DC245), Isoleicosane, vitamin E acetate and film formers are mixed until homogeneous and then milled using a Silverson LART mixer at 9000 rpms to the desired particle size. Next, the preservatives and glycerine and skin conditioning agents are added to the above mixture and mixed until homogenous. The mixture is then heated to a temperature of between 85 - 90°C, at which time the solidifying agent (if used) is

added (melted into the mixture) with mixing until the mixture homogenous. Add the particulate materials to the mixture and mix until homogeneous. The mixture is then cooled to room temperature. Once cooled, the mixture is incorporated into the appropriate package.

## WHAT IS CLAIMED IS:

1. An anhydrous cosmetic composition characterized in that it comprises:
  - (i) from 0.1 to about 30% of emulsifying crosslinked siloxane elastomer, preferably having a particle size of from above 10 to about 200 microns;
  - (ii) from about 10 to about 80% of a solvent for the crosslinked siloxane elastomer;
  - and
  - (iii) at least about 20% of a humectantwherein the compositions contain less than about 1% water.
2. The anhydrous cosmetic composition of Claim 1 that wherein said composition further comprises a conditioning agent selected from the group consisting of exfoliants, emollients and mixtures thereof.
3. The anhydrous cosmetic composition of Claim 1 that further comprises an emulsifier.
4. The anhydrous cosmetic composition of Claim 3 wherein the emulsifier is a polyoxyalkylene copolymer.
5. The anhydrous cosmetic composition of Claim 1 wherein said composition further comprises a pigment.
6. The anhydrous cosmetic composition of Claim 5 wherein the pigment is selected from the group consisting of talc, mica, magnesium carbonate, calcium carbonate, magnesium silicate, aluminum magnesium silicate, silica, titanium dioxide, zinc oxide, red iron oxide, yellow iron oxide, black iron oxide, ultramarine, nylon powder, polyethylene powder, methacrylate powder, polystyrene powder, silk powder, crystalline cellulose, starch, titanated mica, iron oxide titanated mica, bismuth oxychloride, pearl, pearl mica, interference pigments and mixtures thereof.
7. The anhydrous cosmetic composition of Claim 1 wherein said composition is in the form of a foundation, mascara, concealer, eyeliner, brow color, eye shadow, blusher, lip paint or lipstick.

8. An anhydrous cosmetic composition characterized in that it comprises:
- (i) from about 0.1 to about 30% of emulsifying crosslinked siloxane elastomer, preferably having a viscosity of from above 20,000 to about 6,000,000 cps;
  - (ii) from about 10 to about 80% of a solvent for the crosslinked siloxane elastomer;
  - and
  - (iii) at least about 20% of a humectant
- wherein the compositions contain less than about 1% water.
9. The anhydrous cosmetic composition of Claim 1 wherein said composition further comprises an active selected from the group consisting of a sunscreen active, a film forming agent, a shine control agent, and combinations thereof.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
17 January 2002 (17.01.2002)

PCT

(10) International Publication Number  
**WO 02/003933 A3**

- (51) International Patent Classification<sup>7</sup>: **A61K 7/02**, 7/48, 7/021
- (21) International Application Number: **PCT/US01/21614**
- (22) International Filing Date: **9 July 2001 (09.07.2001)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
60/217,170 10 July 2000 (10.07.2000) US  
09/850,961 8 May 2001 (08.05.2001) US
- (71) Applicant: **THE PROCTER & GAMBLE COMPANY**  
[US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).
- (72) Inventors: **VATTER, Michael, Lee**; 4159 California Road, Okeana, OH 45053 (US). **SUNKEL, Jorge, Max**; 460 Fairview Place, Cincinnati, OH 45219 (US). **MOTLEY, Curtis, Bobby**; 8032 St. Matthew Drive, West Chester, OH 45069 (US).
- (74) Agents: **REED, T., David et al.**; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217-1087 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), DE (utility model), DK (utility model), DM, DZ, EC, EE (utility model), ES, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report  
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- (88) Date of publication of the international search report:  
1 August 2002
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



**WO 02/003933 A3**

(54) Title: **ANHYDROUS COSMETIC COMPOSITIONS**

(57) Abstract: An anhydrous skin treatment composition is provided which includes a crosslinked emulsifying siloxane elastomer, at least 20 % humectant and a volatile siloxane. Inclusion of the elastomer provides a non-traditional smooth/silky feel to the skin upon application with a non-draggy rub in.



# INTERNATIONAL SEARCH REPORT

International Application No  
PCT/US 01/21614

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 A61K7/02 A61K7/48 A61K7/021

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 A61K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	FR 2 768 926 A (OREAL) 2 April 1999 (1999-04-02) page 6, line 1 - line 13; claims 1,5,14,17; example 1	1-9
Y	EP 0 608 989 A (PROCTER & GAMBLE) 3 August 1994 (1994-08-03) page 3, line 15 -page 4, line 32; claims 1,2,4,14	1-9
P,A	US 6 103 250 A (HAWKINS GEOFFREY ROBERT ET AL) 15 August 2000 (2000-08-15) column 2, line 45 -column 3, line 6; claims 1,5,7 column 5, line 1 - line 31 column 9, line 21 - line 26	1,5-7

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

**\* Special categories of cited documents :**

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

14 May 2002

Date of mailing of the international search report

22/05/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Angiolini, D

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/21614

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2768926	A	02-04-1999	FR 2768926 A1	02-04-1999
			BR 9804138 A	14-12-1999
			CA 2245989 A1	01-04-1999
			EP 0908175 A1	14-04-1999
			JP 11158030 A	15-06-1999
			PL 328909 A1	12-04-1999
			US 6258345 B1	10-07-2001
			US 2001026811 A1	04-10-2001
EP 0608989	A	03-08-1994	EP 0608989 A2	03-08-1994
US 6103250	A	15-08-2000	AU 6096301 A	14-08-2001
			WO 0156531 A2	09-08-2001